

ATRAZINE USE

Setback Requirements and Restrictions for Standpipes



This information does not substitute the label. **ALWAYS FOLLOW THE LABEL!**

Examples of products and premixes containing atrazine:

Atrazine 4L, Atrazine 90DF, Aatrex 4L, Lumax EZ, Acuron, Breakfree ATZ

Reference to commercial products or trade names is made with the understanding that no discrimination is intended and no endorsement is implied.



In accordance with the Americans with Disabilities Act, this information is available in alternative forms of communication upon request by calling 651-201-6000. TTY users can call the Minnesota Relay Service at 711. The MDA is an equal opportunity employer and provider.

December 2017

ATRAZINE LABEL SETBACK REQUIREMENTS

ATRAZINE LABEL RESTRICTIONS FOR STANDPIPES

in “Terraced” or “Non-Terraced”
Tile-Outletted Fields

No atrazine mixing or loading:

- 50 feet from wells, sinkholes, streams, rivers, lakes, and other water reservoirs.

No atrazine application:

- 50 feet from wells and sinkholes.
- 66 feet from intermittent or perennial streams and rivers or from HELC run-off point.
- 200 feet from lakes and other water reservoirs.

Setback distance must be measured from point where field surface water run-off enters streams or rivers.

Follow one of the restrictions for standpipes:

- Immediately incorporate (mechanical) atrazine to depth of 2-3 inches in the entire tile-outletted field; or
- Use no-till with high residue management in the entire tile-outletted field; or
- Setback atrazine application 66 feet from standpipe.

Read and follow the following information very carefully:

- **Label includes word “terraced”**
Restrictions apply only to terraced fields (most of the atrazine product labels in Minnesota).
- **Label does not have “terraced”**
Restrictions apply to both terraced and non-terraced fields (a few atrazine product labels in Minnesota).

